Rollei

Candela 330 Bi-Color



Candela 330 Bi-Color – Compact bi-color continuous light with powerful performance

- 330 Watt power: Stepless brightness control from 0 to 100% for maximum flexibility for photo and video illumination
- Bi-Color: Adjustable color temperature from 2,700 6,500 K
- Ultra-compact & lightweight: Only 29.9 x 12.8 x 23.2 cm and 2.07 kg for maximum mobility
- Dual power supply: Battery or mains operation for studio or outdoor shooting
- Smart operation: Easy control via app and pairing with additional lights
- · Quick and easy mounting: Bowens mount adapter included for use with light shapers
- Ultra-quiet active cooling: No interference with audio recordings, ideal for content creation
- Intelligent temperature control: For safe operation with only 20 dB in silent mode
- Versatile lighting effects: 10 pre-programmed settings available
- High color fidelity: CRI of 95 and TLCI of 98 for authentic colors









Technical Data	
Number of LEDs	1 COB-LED
Power	330.0 W
Color temperature	2,700 - 6,500 K
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A - G
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	95 + 98 +
Power adjustment	0 - 100 %, in 1-% or 10-%-steps
Illuminance (without reflector)	3,200 K: 41,600 lux (0.5 m), 10,200 lux (1 m), 4,940 lux (1.5 m) 4,500 K: 44,300 lux (0.5 m), 11,000 lux (1 m), 3,980 lux (1.5 m) 5,500 K: 45,500 lux (0.5 m), 11,400 lux (1 m), 5,370 lux (1.5 m)
Light effects	10
Bowens S-Type mount	Yes
Remote control	App and remote control (sold separately)
Radio frequency band	2.400 - 2.480 GHz
Transmission power maximum	10 dBm
Battery operation	2x lithium-ion batteries of the type NP-F or V-mount battery with max. 14.8 W (not included in delivery)
Power supply	Rollei AC/DC adapter for Candela 330 Bi-Color Power supply: Input 100 - 240 V ~ 4.0 A 50 / 60 Hz Output: 48.0 V 5.2 A
Rated input power	360.0 W
Volume cooling fan	25 dBA (100 % brightness, 1 m)
Connections	2 raised guide rails, 2 recessed guide rails, USB-C input, tripod mount with tilt
Illumination angle	120 °
Dimensions (L x W x H) Weight	29.9 x 12.8 x 23.2 cm 2.07 kg

What's in the Box and Packaging Details	
What's in the box	COB continuous light, tripod mount with tilter, protective cap, mains adapter with cable, manual
Packaging dimensions (L x W x H) Weight	XX cm XX kg

Specifications are subject to change without notice. Other trademarks and trade names are the property of their respective owners. Camera / Smartphone etc. not included.



www.rollei.com