

Powerful and Compact Bi-Color Continuous Light with Dual Power Supply

- 60 watts of power: Continuous brightness control from 0 to 100% for maximum flexibility for photo and video lighting
- Bi-Color: Adjustable color temperature from 2,700 - 6,500 K
- Ultra-compact & lightweight: Only 14 x 8 x 9 cm and 550 g for maximum mobility
- Dual power supply: battery or mains operation for studio or outdoor shootings
- Smart operation: Easy to control via iOS app, remote control and pairing with other lights
- Quick and easy installation: Includes Bowens mount adapter for using light shapers
- Ultralight active cooling: No interference with audio recordings, ideal for content creation
- Versatile lighting effects: 10 pre-programmed settings are available
- High color consistency: CRI and TLCI of 97 for authentic colors



Technical Data

Number of LEDs	1
Power	60.0 W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,700 – 6,500 K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI) TN-30-18	97 97 Rf 92 / Rg 105
Power adjustment	0 – 100 %, in 1 %- or 10 % steps
Illuminance (without reflector)	3,200 K: 12,728 lux (0,5 m), 2,807 lux (1 m), 2,297 lux (1.5 m) 4,500 K: 13,407 lux (0.5 m), 2,971 lux (1 m), 2,441 lux (1.5 m) 5,500 K: 13,721 lux (0.5 m), 3,033 lux (1 m), 2,480 lux (1.5 m)
Illumination angle COB light	120 °
Illumination angle reflector	10 °
Flicker-free	Up to 240 fps
Light effects	10
Bowens S-type mount	yes
Remote control	Remote control (not included) or iOS app
Radio frequency band	2.400 – 2.480 GHz
Transmission power maximum	10 dBm
Battery operation	2x Lithium-Ion batteries of type Typ NP-F or V-Mount with max. 14.8 V (not included)
Power supply	Rollei AC/DC Adapter für Candela 60 Bi-Color, Input: AC 100 – 240 V / 1.5 A, 50/60 Hz, Output: DC 20.0 V / 4.5 A
Input:	DC 20.0 V / 4.5 A
Rated input power	80 W
Volume cooling fan	25 dBa (100 % brightness, 1 m)
Connections	COB continuous light: 2 raised guide rails (Nato standard), 2 recessed guide rails (Nato standard); USB-C input Tripod mount with tilt: spigot connection, recessed guide rail (Nato standard)
Dimensions (L x W x H) Weight	14 x 8 x 9 cm 550 g

What's in the Box and Packaging Details

What's in the box	COB continuous light, Bowens S-Type adapter, reflector, tripod mount with tilter, protective cap, mains adapter with cable (3 m), carrying bag, operating instructions
Packaging dimensions (L x W x H) Weight	26 x 19.5 x 19.5 cm 1.635 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners.

Item No.: 20118

