

Powerful and long-running LED light

- ▶ Low power consumption, constant color temperature, long lifespan
- ▶ Illuminance of over 68,000 lx at 0.5 m (with reflector), stepless power setting via rotary control
- ▶ High color accuracy for photographers and filmmakers (CRI > 96, TLCI > 97)
- ▶ Flicker-free light characteristics – ideal for video recordings
- ▶ Bowens S-type bayonet for many light shapers
- ▶ Constant control over the illumination, no disturbing flash light
- ▶ 60 W power, continuously adjustable
- ▶ Color temperature 5500 K
- ▶ Power supply from the mains or battery* – ideal for use in the studio and on the go



Technical data

Area of application	Product / portrait photography and videography
Power	60 W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Lifetime	100,000 hours
Illuminance	With Standard Reflector 55°: 68,310 lx (0.5 m) 11,250 lx (1 m) 4,447 lx (1.5 m) Without reflector: 8,974 lx (0.5 m) 2,370 lx (1 m) 1,127 lx (1.5 m)
Power control	0 – 100 %, in 1 % steps
Color rendering index (CRI)	96+
Color temperature	5500 K ± 200 K
Channels	16 channels (00 – 15)
Groups	10 groups (A – J)
Remote control	integrated, 2,4 GHz
Radio frequencies	2,402 – 2,482 GHz
Bowens S-type Bajonett	Yes
Power supply	100 – 240 V, 50/60 Hz, fuse 2 A
Battery operation	2 lithium-ion batteries NP-F970 (7.4 V / 6600 mAh)*
Battery life	65 minutes at full power
Compatible with trigger	Rollei Pro Radio Transmitter Mark II*
Compatible remote control	Rollei Soluna Remote Control*
Dimensions Weight	24,5 x 12 x 18 cm 1,25 kg (without batteries)
Further equipment	LC display, handle and tripod thread (5/8")
Box content	Soluna II-60, standard reflector 55°, power adapter, protective cap, manual

Specifications are subject to change without notice. *Not included in delivery.