

The Compact Speedlite from Rollei

- Multicompatible hot shoe: Canon, Nikon, Fuji, Panasonic, Olympus, Sony*
- 80 Ws output: Rectangular flash bulb and round flash head with powerful output, adjustable in 9 f-stops
- Seamless integration: Compatible with all Freeze and Studio flashes
- Versatile modes: TTL mode, manual mode, freeze mode, HSS sync, sync to 1st/2nd shutter curtains
- Long-lasting power: Powerful 2,500 mAh lithium-ion battery, over 500 shutter releases on a full charge



Technical Data

Power	80 W / 80 Ws
Guide number	60
Modes	TTL / Manual
Synchronisation modes	Normal / Freeze / HSS
Power adjustment	9 steps (0.1 / 1.0 steps)
Flash duration (t = 0.5 s)	Normal: 1/800 – 1/10.000 s Freeze: 1/1.500 – 1/50.000 s
Recycling time	1.5 sec. (at full power)
Burst mode: pictures per second	Up to 20 shots per sec.
Channels Groups	31 16
Color temperature	5.500 K +/- 150 K
Modeling lamp Adjustment	3 W 3 levels
Receiver	Integrated
Radio frequency band	2.402 – 2.480 GHz
Transmission power maximum	6 dBm
Power supply Battery operation	Power adapter Input: AC 100 – 240 V, 50/60 Hz, 0.5 A max. Output: DC 5.0 V / 3.0 A max., 9.0 V / 2.0 A max., 12.0 V / 1.5 A max. Battery charger Input: DC 5.0 V / 3.0 A max., 15.0 W max. Output: DC 8.4 V / 1.0 A max., 8.4 W max. lithium-ion battery (input: DC 8.4 V / 1.0 A max., 8.4 W max. Kapazität 7.4 V / 18.5 Wh / 2,500 mAh)
Flashes in battery operation	> 500 (at full power)
Additional features	Zoom function, multi-compatible hot-shoe, Canon RT compatibility (99 assignable IDs), firmware update, auto power off, ¼" thread, radio transmitter function
Compatible camera brands	Canon, Nikon, Fuji, Panasonic, Olympus, Sony (Sony cameras via separately available adapter)
Compatible flash triggers	Professional Radio Transmitter, Professional Radio Transmitter Mark II, Professional U7 Radio Transmitter
Dimensions (L x W x H) Weight	19.5 x 7.5 x 6.5 cm 500 g

What's in the Box and Packaging Details

What's in the box	HS Freeze Portable Pro, battery, charger, USB-C cable, power adapter, carrying case, cold shoe stand, manual
Packaging dimensions (L x W x H) Weight	21.5 x 11.5 x 13.0 cm 880 g

Specifications are subject to change without notice. *Only with separately available adapter.

