

Fully equipped permanent light

- ▶ 300 W power continuously adjustable
- ▶ 5500 K color temperature similar to daylight
- ▶ 5 different light effects with 10 frequencies each
- ▶ 32 channels, 16 groups
- ▶ Ideal for video recordings
- ▶ Fan can be switched off (with a max. Power of 30 %)
- ▶ The Soluna 300 pro consists of the light head and the control box, so that it can also be easily operated when mounted on the ceiling, for example
- ▶ Dual power supply (mains or battery* possible)
- ▶ CRI color rendering index over 97 and TLCI over 98
- ▶ Over 207,000 lx illuminance at 0.5 m with reflector
- ▶ App operation
- ▶ DMX 512 operation



Technical data

Power	300 W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Illuminance	With Soluna Standard Reflector 70°: 207,750 lx (0.5 m) 40,860 lx (1 m) 16,440 lx (1.5 m) 8,940 lx (2 m) Without reflector: 47,210 lx (0.5 m) 11,740 lx (1 m) 5,358 lx (1.5 m) 3,050 lx (2 m)
Power control	0 – 100 %, in 1 % steps
Color rendering index (CRI)	97+
Television Lighting Consistency Index (TLCI)	98+
Color temperature	5,500 K ± 200 K
Channels Groups	32 channels (00 – 31) 16 groups (A – J / L / O / P / Q / S / U)
Effects	TV Flickering Bulb Fireworks Thunderstorm mode Blink mode – each has a frequency of 1 to 10
Compatible remote control	Remote control* for Soluna LED permanent lights*
Remote control	Integrated, 2,4 GHz Range > 100 m
Bluetooth®¹⁾ function	Version 4.2 Radio frequencies 2.402 – 2.480 GHz Transmission power max. 6 dBm
Bowens S-type Bajonett	Yes
Power supply	Light head: Input: 56 V DC / Max. 5 A / 280 W Control box: Input: 100 – 240 V AC / 50/60 Hz / Max. 2.9 A / 320 W Input: 14.4 – 33.6 V DC / Max. 10 A / 300 W Output: 56 V DC / Max. 5 A / 280 W
Battery operation	yes, 1–2 V-mount batteries*
More features	Control box with LC display Light head with umbrella holder Tripod attachment Carrying handle U-bracket Cooling fan (can be switched off with a maximum power of 30 %) light angle > 120° DMX 512 control
Dimensions Weight	Light head: 28 x 19 x 20 cm 2.7 kg Control box: 11.5 x 14.5 x 29.5 cm 3.1 kg
Box content	Soluna 300 Pro light head and box, Soluna standard reflector 70°, light stand holder for the control box, protective cap, power adapter (control box – socket), cable (light head – control box), carrying bag, manual

Specifications are subject to change without notice. ¹⁾The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. *Not included in delivery.