

### Mobile BiColor permanent light with 576 LEDs

- ▶ LED permanent light for photo and video recordings
- ▶ Color rendering index (CRI) and Television Lightning Consistency Index (TLCI) of 95+, you can always work in particularly natural light
- ▶ 40 W power, continuously adjustable
- ▶ Color temperature individually adjustable between 3,200 K and 5,500 K
- ▶ Infinitely dimmable brightness (1 – 100 %)
- ▶ Controllable on the panel or remotely using the free Rollei Lumen app
- ▶ Incl. 2 diffusers (soft and CTO) and barn doors to direct the light
- ▶ Dual power supply via power pack or battery\*



### Technical Data

Number of LEDs	576 (288 white light/288 warm light)
Power	40 W
Energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Colour temperature	3,200 – 5,500 K
Colour rendering index	(CRI) 95+
Television Lighting Consistency Index	(TLCI) 95+
Power control	1 – 100%, in 1% steps
Illuminance	5,500 K: 4,709 lx / 0.5 m   3,200 K: 4,376 lx / 0.5 m
Illumination angle	110°
Bluetooth®*	Version 4.0
Frequency band	2.400 GHz – 2.480 GHz
Max. transmitting power	8 dBm
Input	15.0 V = 3.0 A
Power supply	Power supply unit: via mains adapter "Rollei AC/DC Adapter for Rollei Panel 600Bi", Input: 100–240 V ~ 2.5 A   50/60 Hz, Output: 15.0 V = 3.0 A ⚡   Power: 45 W   Protection class: II   Battery operation: 2 lithium-ion batteries of type NP-F970 (7.4 V / 6,600 mAh) or NP-F750 (7.2 V / 4,400 mAh) – not included in the delivery
Rated input power	40 W
Connections	Spigot, Spigot, power supply connection
Dimensions   Weight	31 x 31.5 x 7.3 cm   1.38 kg (without battery)
Box Content	Rollei Lumen Panel 600Bi, 2 diffusers (soft and CTO), AC/DC adapter, user manual

**Note:** Lux were measured at a distance of 0.5 meters.

Subject to technical changes. 1)The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. \*Not included in delivery, optionally available.

