

Compact And Lightweight Studio 500 Studio Flash

- Compact studio flash with 500 watt-second output
- Adjustable in 7 f-stops
- M mode
- Synchronization: Normal
- Burning time up to 1/2,200 s
- Recycling time max. 1.0 s
- 32 channels, 16 groups
- Color temperature of 5,500 K \pm 200 K
- Modeling light: LED 15 W (4,100 K \pm 200 K)
- Bowens S-Type bayonet
- Compatible with Professional Radio Transmitter Mark II



Technical Data

Power	500 Ws
EU energy efficiency class	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Flash modes	Manual
Sync modes	Normal
Output control	M: 3.0 – 9.0 (1/64 – 1/1)
Flash duration (t = 0.5 s)	1/800 – 1/2,200 s
Recycling Time	0.1 – 1.0 s
Channels	32 Channels: 00 – 31
Groups	16 Groups: A/B/C/D/E/F/G/H/I/J/L/O/P/Q/S/U
Colour temperature	5,500 K \pm 200 K
Modelling light	15 W LED (colour temperature: 4,100 K \pm 200 K)
Radio receiver	Integrated / 2.4 GHz / range > 100 m
Bowens S-Type bayonet	Yes
Power supply	AC 195 ~ 245 V 50 / 60 Hz 15 A (fuse)
Compatible radio transmitters	Professional Radio Transmitter Mark II
Compatible cameras	Canon / Nikon / Sony / Fuji / Panasonic / Olympus
Further functions / equipment	LC display Ready indicator (acoustic, optical) Acoustic signal (can be switched off) Photocell on / off Overheating warning "OH" Bowens S-Type bayonet Umbrella holder Tripod mount (5/8") Carrying handle
Dimensions (L x W x H) Weight	27 x 13.5 x 20.5 cm 1.5 kg

Scope of Delivery and Packaging Details

Box Content	Studio 500, protective cap, power cord and operating instructions
Packing dimensions (L x W x H) Weight	25 x 17 x 33 cm 2.38 kg

Specifications are subject to change without notice.

