

**Professional studio flash unit with rechargeable battery –  
Ideal for outdoor shootings**

- ▶ Can be used in a studio or in outdoor use
- ▶ Battery-operated studio flash for high mobility – no cable necessary for power supply
- ▶ Protected against splash water\*, sand\* and dust\*
- ▶ Low recycle time– below 2 seconds but with extreme high flash power up to 600 watt-seconds (Ws)
- ▶ TTL and manual mode
- ▶ High Speed Sync up to 1/8000 second
- ▶ Freeze mode up to 1/19000 second
- ▶ Synchronization on the front and rear curtain
- ▶ Control via radio transmitter, radio transmitter supported by App (can be downloaded for free)
- ▶ Easy to transport in the bag
- ▶ Bowens connection for high compatibility with accessories



<b>IPX3</b> Splash water, sand & dust protected	<b>GN80</b> Guide Number ISO 100	 Freeze 1/19000s	 1/8000 seconds	 Mobile Flash
 High flash power 600 Ws	 Sync 1st and 2nd shutter	<b>20W</b> LED modeling light	 Li-Ion Akku 6 Ah	<b>24</b> Months Warranty and Replacement

**Technical Data**

<b>Flash Power</b>	600 Ws
<b>Flash Power Range</b>	9 stops (in 0.1F or 1.0F increments)
<b>Guide Number</b>	80 (with ISO 100, 2 meters and Reflector 55 Degree)
<b>Modeling Light</b>	20 W LED
<b>Recycle Time</b>	Approx. 1.9 seconds
<b>Flash Duration</b>	Normal: 1/800s – 1/8000s   Freeze: 1/800s – 1/19000s
<b>Lighting Time</b>	Up to 500 (if battery is fully charged)
<b>Temperature</b>	5500 ± 150K (normal mode)   5500 ± 800K (Freeze mode)
<b>IPX3*</b>	Splash water, sand and dust protection
<b>Operation modes</b>	TTL, M (manual), Easy Cap, Delay
<b>Flash modes</b>	Normal   High Speed Sync   Freeze
<b>Channels   Groups</b>	0 – 15   A, B, C, D, E, F
<b>Radio Range</b>	Up to 300 meters (built-in radio receiver)
<b>Infrared Sensor</b>	Integrated (IR slave function)
<b>Connections</b>	Sync (3,5 mm)   USB (for firmware updates)
<b>Display</b>	Multifunctional LCD (7.2 cm / 2.8")
<b>Power Supply</b>	Exchangeable and rechargeable lithium ion Battery (14.8 V / 6 Ah)
<b>Dimension   Weight</b>	32.5 x 12 x 22.5 cm   3.022 kg / 2.422 kg (with/without battery)
<b>Scope of Delivery</b>	Studio flash light incl. flash tube, protective glass and plastic cover, battery, charging cable, sync cable, bag, manual

Subject to technical changes.  
\*This only applies for the aluminum body, the front of the flash (flash tube) is excluded.