

### Professional Flash Unit

- ▶ Integrated 2.4 GHz receiver
- ▶ **Guide number 56** (ISO 100, 180 mm)
- ▶ High speed synchronisation up to 1/8.000 sec.
- ▶ TTL Flash mode
- ▶ Manual mode
- ▶ Master/Slave mode
- ▶ Strobe flash mode
- ▶ Rear-curtain synchronisation



### Scope of Delivery

Rollei Pro Flash Unit 56F for Sony, Protective bag, Micro base, Soft box, USB cable and User manual

### Technical Features

<b>Guide Number</b>	56 (ISO 100, 180mm)
<b>Motorised Zoom</b>	18 – 180 mm; manual / automatic zoom
<b>TTL Flash Mode</b>	TTL, M, 2.4 G Master, 2.4 G Slave, S1, S2, Multi
<b>Wireless Trigger</b>	2.4 G wireless flash, light pulse, S1/S2 optical flash
<b>WL Visual Flash Distance</b>	Indoor up to 30 meters   Outdoor up to 50 meters
<b>WL Transmission Range 2.4 GHz</b>	Up to 50 meters
<b>Swivel Reflector</b>	Tilt angle (up and down): -7° up to +90° Rotation angle (left and right): 0° up to +180°
<b>Slave Group and Unit</b>	16 Slave communication channels (1 – 16) 3 Slave unit groups (A,B,C)
<b>Color Temperature</b>	5500 K
<b>Flash Duration</b>	1/200 seconds ~ 1/20,000 seconds
<b>High Speed Synchronisation</b>	Up to 1/8,000 seconds
<b>Flash Control</b>	1/128 – 1/1 step length is 0.3 EV, total 22 fine-tuning gear
<b>Peripheral Interface</b>	Hot shoe, PC sync, USB (for firmware updates only)
<b>Recycle Time</b>	3.0 seconds
<b>Power</b>	4x AA batteries or 4x AA Ni-MH batteries (any batteries are not included)
<b>Lighting Time</b>	100 ~ 1500 times
<b>Additional Function</b>	Sleep mode, overheating protection
<b>Dimensions   Weight</b>	WxHxD: 75 x 200 x 60 mm   399 g (without any batteries)

Subject to technical changes. Sony is registered trademark, Sony products are trademarks or registered trademarks of Sony.