

### Professional Flash Unit

- ▶ Dual mode – the flash is compatible with Canon and Nikon cameras
- ▶ Guide number 58 (ISO 100, 180 mm)
- ▶ High speed synchronisation up to 1/8.000 seconds
- ▶ TTL Flash mode
- ▶ Manual mode
- ▶ Master/Slave mode
- ▶ FEB (flash bracketing)
- ▶ Strobe flash mode
- ▶ Rear-curtain synchronisation
- ▶ Permanent LED light for checking shadows as well as fill light
- ▶ Rechargeable lithium ion battery included
- ▶ NiMH rechargeable battery (AA) operation possible



### Scope of Delivery

Rollei Flash Unit 58, Protective Bag, Micro Base, Soft Box, Rechargeable Lithium Ion Battery, Charger, AC Cable, AA Battery Holder and User Manual

### Technical Features

Guide Number	58 (ISO 100, 180 mm)
Motorised Zoom	18 - 180 mm, manual / automatic zoom
TTL Flash Mode	Automatic mode, manual mode M, stroboscopic mode multi, LED lighting, canon master, Nikon master models, slave light SLAVE c, SLAVE n, light flash mode S1, S2, surrounded by flash exposure (FEB)
Wireless Trigger	Light pulse, induction flash light
Wireless Transmission Range	Indoor up to 30 meters   Outdoor up to 15 meters
Swivel Reflector	Tilt angle : -7° up to +90° Rotation angle left / right: 0° up to +180°
Slave Group and Unit	4 Slave channels (1, 2, 3, 4)   3 Slave groups (A, B, C)
Color Temperature Flash	5500K
LED Colour Temperature	5500 ± 200 k colour (white)
LED Power	3W
Flash Duration	1/200 seconds – 1/20,000 seconds
High Speed Synchronisation	Up to 1/8,000 seconds
Manual Flash Control	1/128 - 1/1 step 0.3 EV, a total of 22 grade fine-tune gear
External Interface	Hot Shoe, PC sync interface, external interface DC power supply
Recycle Time	2.3 seconds
Power Supply	4 AA rechargeable batteries (NiMH 1.2 V / not included), 7.4 V lithium ion battery, external 6–8 V DC power supply
Quantity of Flashes	500 – 5000 times (batteries/rechargeable)
Additional Features	Power saving mode, sleep mode, overheating protection
Size   Weight	BxHxT: 70 x 200 x 65 mm   460 g (without any batteries)

