

Anglerfish SL1 60DN Bundle

Most Accurate Color Consistency with 70 Watts

- Highest levels of color consistency for consistent illumination of your motif
- Continuous LED Light with daylight-accurate characteristics, emitting light that reduces blue light and thus reproduces the light spectrum of the sun incomparably well
- Daylight-like light (5.600 K) on the set with an illuminance of 12.200 lx (5.600 K, 1 m, with reflector included in the set)
- Settings on the device or via the free iFootage Lumin app
- Synchronization of several iFootage Anglerfish LED continuous lights via the iFootage Lumin App
- Extensive scope of delivery incl. reflector, spigot adapter and transportation bag









Technical Data	
Number of LEDs	1 (COB LED)
Power	70 W
Color temperature	5.600 K ± 200 K
Color Rendering Index (CRI) Television Lighting Consistency Index (TLCI)	98+ 99+
Power adjustment	0 – 100 % in 0.1 % steps
Illuminance	With reflector (55°): 12.200 lx (5.600 K, 1 m) Without reflector: 3.000 lx (5.600 K, 1 m)
Illumination angle	120 °
Light effects	8
Bowens S-type mount	Mini Bowens Mount
Remote control	Via iFootage Lumin app
Bluetooth®* version	5.1
Radio frequency band	2.400 – 2.480 GHz
Maximum transmission power	8 dBm
Operating range Bluetooth®*	15 m
Power supply	Via AC/DC adapter, input: AC 100 – 240 V 50/60 Hz, output: DC 20.0 V / 4.5 A
Rated input power	90 W
Volume cooling fan	< 30 dB
Connections	Power supply, tripod mount
Working temperature	-15° C – 45° C
Dimensions (L x W x H) Weight	15.4 x 15.2 x 9.6 cm (without reflector; reflector: 11 cm x \varnothing 14 cm) 760 g
What's in the Box and Packaging Details	

What's in the Box and Packaging Details

What's in the box

iFootage Anglerfish SL1 60DN, AC/DC adapter with cable (5 m), power cable (5 m), reflector (55°), light stand adapter, transportation case, manual

Packaging dimensions | Weight 38.3 x 20.8 x 23 cm | 3.2 kg

Specifications are subject to change without notice. *The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners.