## Rollei

## Soluna 500 Pro LED permanent light



## www.rollei.com

## Fully equipped permanent light

- > 500 W power continuously adjustable
- > 5500 K color temperature similar to daylight
- > 5 different light effects with 10 frequencies each
- Ideal for video recordings
- App operation
- Fan can be switched off (with a max. Power of 30 %)
- The device consists of the light head and the control box, so that it can also be easily operated when mounted on the ceiling, for example.
- Dual power supply (network operation or battery\* possible)
- CRI color rendering index over 97 and TLCI over 98
- Over 357,000 lx illuminance at 0.5 m with reflector
- > 32 channels, 16 groups
- Compatible with Soluna Remote Control\*
- DMX 512 operation

Technical data	
Power	500 W
Energy efficiency class (EU 2017/1369)	F
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Illuminance	With Soluna Standard Reflector 70°: 357,600 lx (0.5 m)   61,080 lx (1 m)   25,000 lx (1.5 m)   13,230 lx (2 m) Without reflector: 84,980 lx (0.5 m)   19,190 lx (1 m)   8,595 lx (1.5 m)   4,745 lx (2 m)
Power control	0 – 100 %, in 1 % steps
Color rendering index (CRI) Television Lighting	97+
Consistency Index (TLCI)	98+
Color temperature	5,500 K ± 200 K
Channels   Groups	32 channels (00 – 31)   16 groups (A – J / L / O / P / Q / S / U)
Effects	TV   Flickering Bulb   Fireworks   Thunderstorm mode   Blink mode – each has a frequency of 1 to 10
Compatible remote control	Remote control* for Soluna LED permanent lights*
Remote control	Integrated, 2,4 GHz Range > 100 m
Bluetooth <sup>®1)</sup> function	Version 4.2   Radio frequencies 2.402 – 2.480 GHz   Transmission power max. 6 dBm
Bowens S-type Bajonett	Yes
Power supply	Light head: Input: 105 V DC / Max. 5 A / 525 W   Control box: Input: 100 – 240 V AC / 50/60 Hz / Max. 4.8 A / 530 W   Input: 21.6 – 33.6 V DC / Max. 10 A / 500 W   Output: 105 V DC / Max. 5 A / 530 W
Battery operation	yes, 1–2 V-mount batteries*
More features	Control box with LC display   Light head with umbrella holder   Tripod attachment   Carrying handle   U-bracket   Cooling fan (can be switched off with a maximum power of 30 %)   light angle > 120°   DMX 512 control
Dimensions I Weight	Light head: 28 x 19 x 20 cm l 3.5 kg Control box: 11.5 x 14.5 x 31.5 cm l 3.4 kg
Box content	Soluna 500 Pro light head and box, Soluna standard reflector 70°, light stand holder for the control box, protective cap, power adapter (control box – socket), cable (light head – control box), carrying bag, manual

Specifications are subject to change without notice. <sup>1)</sup>The Bluetooth<sup>®</sup> word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under license. Other trademarks and trade names are the property of their respective owners. \*Not included in delivery.

