Rollei

LUMIS COB 40W Bi-Color



Compact COB Continuous Light with 40 Watt and Integrated Battery

- Ultra-compact: Very small LED COB continuous light
- Latest technology: COB technology for particularly bright light
- Creative shootings: With a handle for moving light
- Integrated battery: Ideal for on location
- Additional accessories: Includes reflector and diffuser







Technical Data	
Number of LEDs	1
Power	40.0 W
EU energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A – G
Color temperature	2,500 – 6,500 K
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	95+ 95+
Power adjustment	0 – 100 %, in 1 % steps
Illuminance (without reflector)	3,200 K: 3,142 lux (0,5 m), 953 lux (1 m), 480 lux (1.5 m) 4,500 K: 3,998 lux (0.5 m), 1,003 lux (1 m), 458 lux (1.5 m) 5,500 K: 9,701 lux (0.5 m), 1,116 lux (1 m), 567 lux (1.5 m)
Illumination angle COB light	120 °
Illumination angle reflector	55 °
Flicker-free	Up to 240 fps
Light effects	8
Bowens S-type mount	No
Volume cooling fan	34.17 dBA (100 % brightness, 1 m)
Power supply	Rollei AC/DC adapter for LUMIS COB 40W Bi-Color Power supply: Input AC 100 – 240 V / 1.7 A 50 / 60 Hz Output: DC 19.0 V / 3.4 A, 65.0 W or Integrated Lithium-ion battery (14.8 V / 3,400 mAh / 50.32 Wh)
Input	DC 19.0 V / 3.4 A
Rated input power	41.0 W
Connections	COB: 1/4" thread, reflector connection, power supply connection Handle: 1/4" thread, 1/4" screw
Dimensions (L x W x H) Weight (light body)	10.2 x 8.5 x 8.5 cm 470 g
What's in the Box and Packaging Details	

COB continuous light, reflector, diffuser, handle, ball head, bag, power supply unit with mains cable

(2.8 m), user manual 21 x 20 x 13.5 cm | 1.03 kg

Specifications are subject to change without notice.

Packaging dimensions (L x W x H) | Weight



What's in the box