

Mobile RGB LED Panel for Photo and Video Shootings

- 480 LEDs (160 warm white LEDs, 160 cool white LEDs, 160 RGB LEDs)
- Power of 30 W, brightness continuously adjustable from 0 – 100 %
- Color temperature adjustable from 2,500 to 9,000 K
- Power supply via mains cable or battery operation
- Easy control at the panel or via remote control



Technical Data - Panel

Number of LEDs	480 (160 warm white LEDs, 160 cool white LEDs, 160 RGB LEDs)
Power	30.0 W
EU energy efficiency class (EU 2017/1369)	G
EU energy efficiency class spectrum (EU 2017/1369)	A - G
Color temperature	2,500 – 9,000 K
Color shades	360
Color Rendering Index (CRI)	98+
Television Lighting Consistency Index (TLCI)	98+
Power/brightness	0 – 100 %
Illuminance	2,188 lx (0.5 m bei 5,500 K)
Light effects	20
Illumination angle	120°
Power supply	Mains operation: Power Supply for LUMIS Panel 600 RGB, input: 100 – 240 V ~ 1.8 A / 50/60 Hz, output DC 12.0 V / 3.0 A / 36.0 W Battery operation: 2x lithium-ion batteries type NP-F550, NP-F750, NP-F970
Anschlüsse	Power connection, 2x battery connection, 2x ¼-inch thread, light stand connection
Dimensions Weight	28 x 26.7 x 4.6 cm 1.225 kg

Technical Data – Remote Control

Max. range	30 m
Channels	7
Bluetooth®* version	4.0
Frequency band	2.402 – 2.480 GHz
Max. transmission power	6 dBm
Power supply	Lithium-ion battery (3.7 V / 500 mAh / 1.85 Wh), input DC 5.0 V / 0.5 A
Battery charging time	Ca. 60 min.
Battery operation time	Ca. 30 days
Dimensions Weight	8.5 x 4.5 x 1.4 cm 63 g

What's in the box and packaging details

What's in the box	LUMIS Panel 600 RGB, diffuser, remote control, power cable with power supply, USB-C cable, bag, user manual
Packaging dimensions (L x W x H) Weight	35 x 30 x 8 cm 1.737 kg

Specifications are subject to change without notice.

*The Bluetooth® word mark and logos are registered trademarks of the Bluetooth SIG, Inc. and any use of such marks by Rollei is under licence. Other trademarks and trade names are the property of their respective owners.

Item No.: 28634



4 048805 286348