LUMIS Slim LED M

## G <sup>A</sup><sub>G</sub>

## Slim LED RGB light wth built in battery

- Three available modes: CCT, RGB and effect mode (7 types of effects with 3 variations each)
- High quality aluminum housing
- Intuitive and easy operation
- Long battery running time

Rollei

- Setting of the color temperature (2.500 9.900 K), the color values (0-360°) and their saturation (0-100)
- Stepless dimmable brightness (1-100%)
- High-contrast OLED display to show the selected settings, the battery level as well as the remaining running hours







Camera not included

## **Technical Data**

| Number of LEDs  | 276 (90 white light / 90 warm light / 96 RGB)  |
|---|--|
| Power   | 18.5 W   |
| Color temperature   | 2.500 – 9.900 K  |
| Energy efficiency level   | G  |
| Spectrum energy efficiency level  | A - G  |
| Colour Hues   | 360  |
| Color rendering index (CRI)   | 95+  |
| Power adjustment  | Flexibly adjustable, 1 – 100%  |
| Illuminance   | 1.300 lux (0.5 m at 9.900 K)   |
| Light effects   | 21   |
| Battery operation   | Rechargeable Lithium Polymer Battery (3.7 V, 10.000 mAh, 37 Wh), Input max. DC 5 V / 2 A             |
| Connections   | USB-C Input (DC 5 V / 2 A), USB-A Output (DC 5 V / 2 A), 3x $^{1\!\!/}_{4}$ screw thread             |
| Additional features   | Power bank: USB-A Output DC 5 V / 2 A  |
| Dimensions   Weight   | 200 x 121 x 13,7 mm (diagonal plane: 8,7") l 511 g   |
| What's in the Box and Packaging Details   |  |
| What's in the Box   | Slim LED M, ball head with ¼" screw thread and cold shoe with<br>¼" screw, 1.8 m USB-C cable, manual |
| Packaging dimensions   Weight<br>Specifications are subject to change without notice. | 149 x 42 x 287 mm   868 g  |

