

- ▶ Range up to 50 m
- ▶ Easy handling
- ▶ Easy-to-read LCD with backlight
- ▶ Timer remote control for: starting time (start of shooting), exposure time, intervall timer up to 100 hours in advance
- ▶ Adjustable exposure time between 1 second up to 100 hours
- ▶ Manually controlled exposure with time indication on the LCD
- ▶ Exposure control with additional sound signal
- ▶ Continuous shooting: 1 up to 399 photos
- ▶ Time interval recording with endless shots



## Technical Features

- ▶ Length of connection cable (from receiver to camera): 20 cm
- ▶ Dimensions: transmitter: approx. 106 x 46 x 27 mm
- ▶ Dimensions: receiver: approx. 64 x 38 x 35 mm
- ▶ Weight transmitter: approx. 49 g (without batteries)
- ▶ Weight receiver: approx. 30 g (without batteries)

## Compatible Camera Models

### Olympus

E-M10, E-M10 Mark II, E-M5, E-M5 Mark II, E-M1, PEN-F, E-P5, EP-L5, EP-L6, EP-L7, EP-L8, E5, E1, E-20P, E-10, E100 Serie, C-8080W, E3, E20, E20N, E330, E500, C5060, C2500L, E-620, E-30, E-PM, E-PL Series, E-510, E-P1, E-410, SP-560UZ, SP-810UZ, XZ-1, EP-2, EP-1, E600, E550, E520, E510, E450, E420, E410, E400, SP-590UZ, SP-570UZ, SP-565UZ, SP-560UZ, SP-550UZ, SP-510UZ, STYLUS SH-1, STYLUS 1, XZ-1

## Scope of Delivery

Remote transmitter and receiver, adapter cable for receiver, AAA batteries for transmitter, CR2 battery for receiver and user manual

Subject to technical changes.

