

Professional studio flash unit

- ▶ Affordable entry into portrait photography
- ▶ Flash power up to 400 watt-seconds (Ws)
- ▶ Low recycle time – below 1 seconds
- ▶ 15 Watt LED Modeling Light
- ▶ Extensive manual settings
- ▶ Easy product photography with Mask Pattern
- ▶ Integrated infrared sensor
- ▶ Creative compose with different color slides
- ▶ Bowens connection for high compatibility with accessories



GN66
Guide Number
ISO 100

15 W
LED modeling
light

Technical Data

Flash Power	400 Ws
Flash Power Range	7 stops (in 0.1F or 1.0F increments)
Guide Number	66 (with ISO 100)
Modeling Light	15 W LED
Recycle Time	Approx. 0.9 seconds
Flash Duration	Normal: 1/800s – 1/2200s
Temperature	5500 ± 200K
Operation modes	M (manual), Mask Pattern
Channels Groups	0 – 15 A, B, C, D, E, F, G, H, I, J
Radio Range	Up to 300 meters
Infrared Sensor	Integrated for Master Slave function
Connections	Sync (3.5 mm)
Display	LCD (4,3 cm / 1,7")
Operating Voltage	AC 195 ~ 245 V 50/60 Hz 5 A Fuse
Dimension Weight	29 x 11.5 x 12.5 cm 1.314 kg
Scope of Delivery	Studio flash light incl. flash tube, plastic cover, reflector, 5 magnetic colour gels and manual

Subject to technical changes.