

**Professional studio flash unit with rechargeable battery –
Ideal for outdoor shootings**


- ▶ Can be used in a studio or in outdoor use
- ▶ Battery-operated studio flash for high mobility – no cable necessary for power supply
- ▶ Protected against spraying water*, sand* and dust*
- ▶ Low recycle time– below 2 seconds but with extreme high flash power up to 600 watt-seconds (Ws)
- ▶ TTL and manual mode
- ▶ High Speed Sync up to 1/8000 second
- ▶ Freeze mode up to 1/19000 second
- ▶ Synchronization on the front and rear curtain
- ▶ Control via radio transmitter, radio transmitter supported by App (can be downloaded for free)
- ▶ Easy to transport in the bag
- ▶ Bowens connection for high compatibility with accessories



IP33

Protected against spraying water, sand and dust*

Stabil colour temperature
5500K
± 150K



IP33
Spray water, sand & dust protected

GN80
Guide Number ISO 100

Freeze 1/19000s

1/8000 seconds

Mobile Flash

High flash power 600 Ws

Sync 1st and 2nd shutter

20W
LED modeling light

Lithium polymer battery 6 Ah

Technical Data

Flash Power	600 Ws
Flash Power Range	9 stops (in 0.1F or 1.0F increments)
Guide Number	80 (with ISO 100, 2 meters and Reflector 55 Degree)
Modeling Light	20 W LED
Recycle Time	Approx. 1.9 seconds
Flash Duration	Normal: 1/800s – 1/8000s Freeze: 1/800s – 1/19000s
Lighting Time	Up to 500 (if battery is fully charged)
Temperature	5500 ± 150K (normal mode) 5500 ± 800K (Freeze mode)
IP33*	Spray water, sand and dust protection
Operation modes	TTL, M (manual), Easy Cap, Delay
Flash modes	Normal High Speed Sync Freeze
Channels Groups	0 – 15 A, B, C, D, E, F
Radio Range	Up to 300 meters (built-in radio receiver)
Infrared Sensor	Integrated (IR slave function)
Connections	Sync (3,5 mm) USB (for firmware updates)
Display	Multifunctional LCD (7.2 cm / 2.8")
Power Supply	Exchangeable and rechargeable lithium polymer battery (14.8 V / 6 Ah)
Dimension Weight	32.5 x 12 x 22.5 cm 3.022 kg / 2.422 kg (with/without battery)
Scope of Delivery	Studio flash light incl. flash tube, protective glass and plastic cover, battery, charging cable, reflector, 5 magnetic colour gels, sync cable, bag, manual

Subject to technical changes.

*This only applies for the aluminum body, the front of the flash (flash tube) is excluded.